

MOLYKOTE® G 68

Plastic gear grease

FEATURES

- High water resistance
- Low coefficient of friction
- Good compatibility with most plastics

COMPOSITION

- Mineral oil
- Polyalphaolefine
- Lithium soap
- EP additives
- Solid lubricants

APPLICATIONS

- Used in gears of electrical toothbrushes and paper shredders.

TYPICAL PROPERTIES

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales representative prior to writing specifications on this product.

Standard*	Test	Unit	Result
Penetration, density, viscosity			
DIN 51 818	NLGI consistency class		2-3
ISO 2137	Worked penetration	mm/10	250-280
ISO 2811	Density at 20°C	g/ml	0.85
DIN 51 562	Base oil viscosity at 40°C	mm ² /s	75
Temperature			
	Service temperature	°C	-30 to +140
ISO 2176	Drop point	°C	190
Load-carrying capacity, wear protection, service life			
Four-ball tester (VKA)			
DIN 51 350 T.4	Weld load	N	1900
DIN 51 350 T.5	Wear scar under 600N load	mm	0.75
	FAG rolling element bearing tester FE 9		
	Almen-Wieland machine, OK load	N	18500
	Fretting corrosion - Deyber tester		
Resistance			
DIN 51 808	Oxidation resistance, pressure drop 100h, 99°C	bar	0.1
Corrosion protection			
DIN 51 802	Emcor method		0
Coefficient of friction			
	Steel ball against plastic surface (POM)		
	Ø ball = 12.7mm, load = 6.3N, v = 10mm/s, 24h	µ	0.014
Oil separation			
DIN 51 817	Oil separation - standard test	%	3.4
Fed-Standard 791-32-2			

* ASTM: American Society for Testing and Materials.
 ISO: International Standardisation Organisation.
 DIN: Deutsche Industrie Norm.

HOW TO USE

How to apply

Clean points of contact. Apply in same way as lubricating greases, using brush, spatula, grease-gun or automatic lubricating device. Suitable for delivery by central lubricating system. In the event of long breaks in service e.g. overnight, the pressure in the delivery equipment should be relieved. Not to be mixed with other greases.

Because of variation in quality of plastics and elastomers, compatibility tests should be carried out for swelling and shrinkage, stress-crack formation, and changes in strength and hardness.

HANDLING PRECAUTIONS

Product safety information required for safe use is not included. Before handling, read product and safety data sheets and container labels for safe use, physical and health hazard information. The material safety data sheet is available on the Dow Corning website at www.dowcorning.com. You can also obtain a copy from your local Dow Corning sales representative or Distributor or by calling your local Dow Corning Global Connection.

USABLE LIFE AND STORAGE

When stored at or below 20°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

PACKAGING

This product is available in 1kg cans, 5kg containers and 25kg pails.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Health,

Environment and Regulatory Affairs specialists available in each area.

For further information, please see our website, www.dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

WE HELP YOU INVENT THE FUTURE.™

www.dowcorning.com