



**Specialty
Lubricants**

**MOLYKOTE® Supergliss
Corrosion protective lubricant**

FEATURES

- Penetration
- Rust loosening properties
- Lubrication
- Corrosion protection

COMPOSITION

- Mineral oil
- Adhesion improver
- Solvent
- Corrosion inhibitors
- Propellant

Lubricating oil with penetrating properties

APPLICATIONS

- Simplify dismantling of rusty components.
- Used as corrosion protection.

TYPICAL PROPERTIES

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales representative prior to writing specifications on this product.

Standard*	Test	Unit	Result
	Color		Bright, transparent
	Density, viscosity		
ISO 2811	Density at 20°C	g/ml	0.83
DIN 51 562	Viscosity at 40°C	mm ² /s	3.6
	Loading capacity, wear protection		
	Four-ball tester		
DIN 51 350 T.2	Weld load	N	1400
DIN 51 350 T.3	Wear scar at 400N load	mm	0.9
	Corrosion protection		
ISO/R 1456	Salt spray test	h	8

* ISO: International Standardisation Organisation
DIN: Deutsche Industrie Norm

HOW TO USE

How to apply

Can be applied by means of a brush, oil-can or spray can or hand-operated spray equipment. When used as a corrosion protection, apply thinly and uniformly to the cleaned areas. Depending on the environmental conditions repeat the process from time to time.

HANDLING PRECAUTIONS

Spray can - Aerosol propellant: CO₂
Pressurised container - protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Combustible.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LOCAL DOW CORNING SALES REPRESENTATIVE.

USABLE LIFE AND STORAGE

When stored at or below 20°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

PACKAGING

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Health, Environment and Regulatory Affairs specialists available in each area.

For further information, please consult your local Dow Corning representative.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Dow Corning specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Unless Dow Corning provides you with a specific, duly signed endorsement of fitness for use, Dow Corning disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.