



Specialty  
Lubricants

**MOLYKOTE® PG 75**  
**High Performance Grease**

**FEATURES**

- Suitable for long-term lubrication
- Good low temperature characteristics (usable down to -40°C)
- Very low coefficient of friction
- Compatible with many plastics and elastomers

**COMPOSITION**

- Mineral oil
- Polyalphaolefine
- Lithium soap
- Solid lubricants

**Lubricating grease for plastic/plastic and plastic/metal combinations with slow to medium-fast movements and light loads**

**APPLICATION**

- Used on vehicle track-rod joints.

**TYPICAL PROPERTIES**

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales representative prior to writing specifications on this product.

Standard	Test	Unit	Result
	Color		Beige
	<b>Consistency, density, viscosity</b>		
DIN 51 818	NLGI consistency class		Approx. 2
ISO 2137	Worked penetration	mm/10	270-300
ISO 2811	Density at 20°C	g/ml	0.86
DIN 51 562	Base oil viscosity at 40°C	mm <sup>2</sup> /s	32
	<b>Temperature</b>		
	Service temperature	°C	-40 to +130
ISO 2176	Drop point	°C	>190
ASTM-D147880	Low temperature torque test at -30°C		
	Initial break-away torque	Nm	222x10 <sup>as</sup>
	Torque after 20 minutes running time	Nm	36x10 <sup>as</sup>
DIN 51 805	Kesternich method - flow pressure at -20°C	mbar	280
	<b>Load-carrying capacity, wear protection, service life</b>		
	Four-ball tester (VKA)		
DIN 51 350 pt.4	Weld load	N	1300
DIN 51 350 pt.5	Wear scar under 400N load	mm	0.8
	<b>Coefficient of friction</b>		
	Steel ball against plastic surface (POM) dia (ball) = 12.7mm; load = 5N; v = 10cm/s, 24h, μ=		0.02
	<b>Corrosion protection</b>		
DIN 51 802	SKF-Emcor method Degree of corrosion		1-2
	<b>Oil separation - evaporation</b>		
DIN 51 817	Standard test	%	4.8
FD 791-32/2	Oil bleeding, 24h, 100°C	%	2.4
FD 791-32/2	Oil evaporation, 24h, 100°C	%	0.2

## **HOW TO USE**

### **How to apply**

Clean points of contact. Apply in same way as lubricating greases, using brush, spatula, grease-gun or automatic lubricating device. Suitable for delivery by central lubricating system. In the event of long breaks in service e.g. overnight, the pressure in the delivery equipment should be relieved. Not to be mixed with other greases.

Because of variation in quality of plastics and elastomers, compatibility tests should be carried out for swelling and shrinkage, stress-crack formation, and changes in strength and hardness.

## **HANDLING PRECAUTIONS**

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LOCAL DOW CORNING SALES REPRESENTATIVE.

## **USABLE LIFE AND STORAGE**

When stored at or below 20°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

## **PACKAGING**

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

## **LIMITATIONS**

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

## **HEALTH AND ENVIRONMENTAL INFORMATION**

To support customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Health, Environment and Regulatory Affairs specialists available in each area.

For further information, please consult your local Dow Corning representative.

## **WARRANTY INFORMATION - PLEASE READ CAREFULLY**

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Dow Corning specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Unless Dow Corning provides you with a specific, duly signed endorsement of fitness for use, Dow Corning disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.