

Technical Data Sheet

VARYBOND White Ceramic Paste 250g/500g/1kg

Description:	VARYBOND Ceramic Paste is a white multifunctional assembly paste based on a solid lubricant that is free from graphite and metal, has high temperature stability and good release properties with a high-quality synthetic oil mix. VARYBOND Ceramic Paste guarantees easy dismantling of the treated parts, even after years. Seizure, stoving or cold welding (e.g. on stainless steel) are prevented as is stick-slipping at creep speed.		
Application:	Preventative treatment against abrasion and reduction of the braking function, squeaking and rattling of the brake system, corrosion of screws and fittings, during spark plug changes, on screw joints on the exhaust and catalytic converter systems, for corrosion protection during engine, gears, axles and exhaust system repairs. Retards damage from acids, alkalis, chemicals, salt and fresh water.		
Instructions:	Clean and degrease surfaces. Apply VARYBOND Ceramic Paste evenly.		
Product Details:	Particle Size:	< 40 µm	
NLGI Consistency:	Class 2-3		
Temperature Range:	-40°C to +1400°C		
Warning:	Wear suitable protective clothing and gloves.		
Content:	VBK 25	250 g	
	VBK 50	500 g	
	VBK 100	1 kg	

The details from this technical product information are based upon our current position of our knowledge, experiences and the legal requirements. They describe the utilisation of our products under normal operating conditions, without the guaranteeing of any laid down characteristics. They do not release the user from the necessity of own examination and precautionary measures. Our guarantee warrants for the quality of the product, but does not cover the success and effects caused by its utilisation, which are dependant upon a multitude of factors.